

Heat Stabilized Ties

CABLE TIE EXPRESS #	LENGTH INCHES	TENSILE STRENGTH	TIE COLOR	PACKAGE QUANTITY	CARTON QUANTITY	WIDTH INCHES	THICKNESS INCHES	MAX BUNDLE DIA. IN.
---------------------	---------------	------------------	-----------	------------------	-----------------	--------------	------------------	---------------------

18 LB MINIATURE

4-18-HS-1000	3.9	18 lbs	Black	1000	25000	.10	.04	1.0
--------------	-----	--------	-------	------	-------	-----	-----	-----


40 LB INTERMEDIATE

5-40-HS-1000	5.5	40 lbs	Black	1000	20000	.14	.05	1.4
8-40-HS-1000	8.6	40 lbs	Black	1000	10000	.14	.05	2.0

50 LB STANDARD

8-50-HS-100	8.3	50 lbs	Black	100	10000	.18	.05	2.0
8-50-HS-1000	8.3	50 lbs	Black	1000	10000	.18	.05	2.0
11-50-HS-100	10.8	50 lbs	Black	100	5000	.18	.05	3.0
11-50-HS-1000	10.8	50 lbs	Black	1000	5000	.18	.05	3.0
14-50-HS-100	14.0	50 lbs	Black	100	5000	.18	.05	4.0
14-50-HS-1000	14.0	50 lbs	Black	1000	5000	.18	.05	4.0

Temperature rating: -40° F (-40° C) to 221° F (105° C)



Define & Organize

Heat Stabilized Nylon 6/6 cable ties perform effectively in high temperature applications to 221 degrees Fahrenheit. The working temperature range of standard Nylon 6/6 cable ties is -40 degrees Fahrenheit to 185 degrees Fahrenheit.